

# LUNAR™

THE  
**LIGHTEST**  
FIBERGLASS EXTENSION  
**LADDER** IN THE  
WORLD

# 15%

LIGHTER THAN  
ORDINARY  
EXTENSION LADDERS

**REDUCE**  
STRAINS & SPRAINS

**RATED FOR  
PROFESSIONAL USE  
OSHA / ANSI**

Extra Heavy Duty Type IA  
300 lbs  
Special Duty Type IAA  
375 lbs



OPTIONAL CLAW®  
AUTO TIE-OFF SYSTEM



STANDARD SWIVEL FEET  
FLIP FOR SPIKES,  
LAY FLAT FOR RUBBER FOOT.



OPTIONAL  
RATCHET LEVELERS™

NONCONDUCTIVE  
FIBERGLASS SIDE RAILS

**Little  
Giant**  
Ladder Systems

**CLIMB ON**



**OPTIONAL CLAW®**  
AUTO TIE-OFF SYSTEM

**LIMITED ARREST SYSTEMS**  
PROTECTS AGAINST IMPACT FALLS



**LIMITED ARREST**  
PREVENTS CATASTROPHIC FALLS



**RUBBER-LINED CABLE HOOKS AND V-RUNG**  
FOR USE WITH UTILITY POLES & STRANDS



**SIDE-MOUNTED DOUBLE PULLEY**  
30% EASIER TO RAISE THE FLY SECTION



**LADDER MITTS**



**RED "DO NOT STAND" RUNGS**

**1-YEAR WARRANTY / TYPE IA 300 LBS / TYPE IAA 375 LBS**

| Part Number | Model   | Storage Height | Storage Width | Highest Standing Level | Extension Max Height | Storage Depth | Round Rung Width | D-Rung Width | Side Rail Width | Max Reach* | Weight |
|-------------|---------|----------------|---------------|------------------------|----------------------|---------------|------------------|--------------|-----------------|------------|--------|
| 15644-560   | 20' IAA | 10' 7"         | 17-1/2"       | 13' 3"                 | 17' 7"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 19' 9"     | 44 lbs |
| 15644-567   | 20' IAA | 10' 7"         | 17-1/2"       | 13' 3"                 | 17' 7"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 19' 9"     | 52 lbs |
| 15645-560   | 24' IAA | 12' 8"         | 17-1/2"       | 17' 3"                 | 21' 7"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 23' 9"     | 50 lbs |
| 15627-567   | 24' IAA | 12' 8"         | 17-1/2"       | 17' 3"                 | 21' 7"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 23' 9"     | 57 lbs |
| 15646-560   | 28' IAA | 14' 7"         | 17-1/2"       | 21'                    | 25' 7"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 27' 6"     | 55 lbs |
| 15628-567   | 28' IAA | 14' 7"         | 17-1/2"       | 21'                    | 25' 8"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 27' 6"     | 62 lbs |
| 15629-560   | 32' IAA | 16' 7"         | 18-1/4"       | 24' 11"                | 29' 7"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 31' 5"     | 72 lbs |
| 15629-567   | 32' IAA | 16' 7"         | 18-1/4"       | 24' 11"                | 29' 7"               | 7.5"          | 1-1/4"           | 1-5/8"       | 3-5/16"         | 31' 5"     | 79 lbs |

Ladder includes: -560 Standard -567 Includes Claw

\*A 5'6" person with a 12" vertical reach